

Standard Filter Housings

The Pumpmasters range of Standard Filter Housings are available in two lengths: 10 or 20 ”.

The 10” housing is normally supplied with a clear bowl, and the 20” in blue, both housings have an integral wall brackets (other configurations available on request).

Standard port size: 3/4” BSP.

Options:

- No wall bracket, or separate bracket.
- Pressure Gauge.
- Optional port sizes 1/4”, 3/8”, 1/2”, BSP or Push Fit.
- Without pressure release button.



The housings are suitable for use with 9 7/8, 10 or 20” cartridges, 3.1” diameter, with either DOE, or Seal Safe O ring sealing.

Model	Part Number	Maximum Dimensions	Initial ΔP @ Flow Rate
10	66-19H-10	337 x 137 mm	0.07 bar @ 18 L/M
20	66-19H-20	597 x 164 mm	0.07 bar @ 38 L/M

Materials of Construction

- *Housing:* Polypropylene (blue) or Styrene Acrylonitrile (clear)
- *Cap:* Polypropylene
- *Button Assembly:* Stainless Steel, Polypropylene and EPDM
- *O-Ring:* Buna-N
- *Maximum Temperature:* 51.7°C
- *Maximum Pressure:* 8.62 Bar

CAUTION: Protect against freezing to prevent cracking of the filter and water leakage



PUMPMASTERS LTD

UNIT 14A, NASMYTH COURT
HOUSTON IND. ESTATE
LIVINGSTON, EH54 5EG
SCOTLAND, UK

TEL : 01506 668740
FAX : 01506 668741